



## AMERICAN INTERNATIONAL INDUSTRIES

### Safety Data Sheet

### Nail Tek Quicken Top Coat

---

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### Product identifier

Product name Nail Tek Quicken Top Coat

Product number 84863, 55824, 55825 found in kit 55844

##### Other means of identification

Use: Cosmetic/Nail Hardener/Sundry Only

##### Details of the supplier of the safety data sheet

Name American International Industries

Address 2220 Gaspar Ave  
Los Angeles, CA 90040  
USA

Telephone 323-728-2999

##### Emergency telephone number

Chem-Tel 1-(800) 255-3924

---

#### SECTION 2: Hazards identification

##### Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008 (CLP)

- Eye damage/irritation (chapter 3.3), Cat. 2, H319
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H335, H336
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

##### Label elements

##### Labeling according to Regulation (EC) No 1272/2008 [CLP]

##### Hazard pictograms



# Safety Data Sheet

## Nail Tek Quicken Top Coat

### Signal word

**Danger**

### Hazard statement(s)

H319  
H335  
H336  
H225

Causes serious eye irritation  
May cause respiratory irritation  
May cause drowsiness or dizziness  
Highly flammable liquid and vapor

### Precautionary statement(s)

P261  
P271  
P280  
P304+P340  
P305+P351+P338

P312  
P337+P313  
P403+P233  
P405  
P210

P233  
P240  
P241  
P242  
P243  
P303+P361+P353

P403+P235

Avoid breathing dust/fume/gas/mist/vapours/spray.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
Call a POISON CENTER/doctor/... if you feel unwell.  
If eye irritation persists: Get medical advice/attention.  
Store in a well ventilated place. Keep container tightly closed.  
Store locked up.  
Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
Store in a well ventilated place. Keep cool.

## SECTION 3: Composition/information on ingredients

### Mixtures

### Components

| Component  | Concentration    |
|--|------------------|
| <b>BUTYL ACETATE (CAS no.: 123-86-4; EC no.: 204-658-1; Index no.: 607-025-00-1)</b>   | <b>40 - 60 %</b> |
| CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3.<br>HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.  |                  |
| <b>ETHYL ACETATE (CAS no.: 141-78-6; EC no.: 205-500-4; Index no.: 607-022-00-5)</b>   | <b>10 - 25%</b>  |
| CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness. |                  |
| <b>ISOPROPYL ALCOHOL (CAS no.: 67-63-0; EC no.: 200-661-7; Index no.: 603-117-00-0)</b>  | <b>10 - 20 %</b> |
| CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness. |                  |

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes

Consult a physician. Show this safety data sheet to the doctor in attendance.  
Move out of dangerous area.

## Safety Data Sheet

### Nail Tek Quicken Top Coat

|                                    |   |
|------------------------------------|---|
| Following inhalation               | Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. |
| Following skin contact             | Wash off with soap and plenty of water. Get medical attention if symptoms occur.  |
| Following eye contact              | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.                                      |
| Following ingestion                | Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. |
| Self-protection of the first aider | Full protective equipment, including self-contained breathing apparatus is recommended.                                     |

#### Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

#### Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

#### Extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### Advice for firefighters

Use NIOSH approved self-contained breathing apparatus in the pressure demand mode. Isolate fire area. Remove all personnel.

#### Further information

Containers exposed to extreme heat may rupture. Water from fog nozzle may be used to cool containers to prevent pressure build up. Vapors are heavier than air and may travel along the ground to a source of ignition.

---

## SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### Environmental precautions

Should not be released into the environment.

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### Methods and material for containment and cleaning up

Large spills or leaks should be cleaned up by trained personnel using properly planned procedures. Protective equipment should be used. Remove or turn off all sources of ignition, such as, but not limited to, gas heaters, gas stoves, sparks from static electricity, or internal combustion engines (gas forklifts). Ventilate area. Use non-sparking tools. Clear affected area of non-essential personnel. Prevent skin contact and breathing vapors. Prevent product from entering sewers or confined areas. Clean area thoroughly. Follow Local, State and U.S. federal waste disposal regulations. Do not incinerate in closed containers.

---

## SECTION 7: Handling and storage

# Safety Data Sheet

## Nail Tek Quicken Top Coat

### Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

### Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

### Specific end use(s)

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

---

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### CAS: 123-86-4

Butyl-acetate

Cal/OSHA: 150 ppm, (ST) 200 ppm PEL inhalation; NIOSH: 150 ppm, (ST) 200 ppm REL inhalation; OSHA: 150 ppm PEL inhalation; 710 mg/m<sup>3</sup> PEL inhalation

#### CAS: 141-78-6

Ethyl acetate

Cal/OSHA: 400 ppm PEL inhalation; NIOSH: 400 ppm REL inhalation; OSHA: 1400 mg/m<sup>3</sup> PEL inhalation

#### CAS: 67-63-0

Isopropyl alcohol

Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m<sup>3</sup> PEL inhalation

### Exposure controls

#### Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### Personal protection equipment

#### Eye and face protection

Eye/Face Protection: None required with normal household use. Industrial Setting: For splash protection, use chemical goggles. Eye wash fountain is recommended.

#### Skin protection

Distribution, Workplace and Household Settings: No special protective equipment required. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Wear suitable protective clothing.

#### Respiratory protection

Distribution, Workplace and Household Settings: No special protective equipment required. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): In case of insufficient ventilation wear suitable respiratory equipment

### Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## **SECTION 9: Physical and chemical properties**

### **Information on basic physical and chemical properties**

|   |                          |
|---|--------------------------|
| Appearance                              | Clear Liquid             |
| Odor                                    | Solvent                  |
| Odor threshold                          | Not Available            |
| pH                                      | Not Applicable           |
| Melting point / freezing point          | Not Available            |
| Initial boiling point and boiling range | 171 - 640 F (77 - 338 C) |
| Flash point                             | -10 C (14 F)             |
| Evaporation rate                        | Slower than Ether        |
| Flammability (solid, gas)               | Flammable                |
| Upper/lower flammability limits         | LEL: 1.7% - UEL: 12.0%   |
| Vapour pressure                         | 100                      |
| Vapour density                          | Not Available            |
| Relative density                        | Not Available            |
| Solubility                              | Moderate                 |
| Partition coefficient: n-octanol/water  | Not Available            |
| Auto-ignition temperature               | Not Available            |
| Decomposition temperature               | Not Available            |
| Viscosity                               | 140 - 240                |
| Explosive properties                    | Not Available            |
| Oxidizing properties                    | Not Available            |
| Specific Gravity                        | 0.900 – 0.930            |

---

## **SECTION 10: Stability and reactivity**

### **Reactivity**

None under normal use conditions.

### **Chemical stability**

Do not store over 120 Degrees F (48 Deg C) and incompatible chemicals.

### **Incompatible materials**

Acids, Alkalies, and Peroxides

### **Hazardous decomposition products**

Methane, Aldehydes, Hydrogen Cyanide, CO, CO<sub>2</sub>, Nitrous Oxides, smoke

---

## **SECTION 11: Toxicological information**

### **Information on toxicological effects**

#### **Acute toxicity**

Vapors may cause drowsiness and dizziness.

#### **Skin corrosion/irritation**

Causes skin irritation and exposure to the skin can cause dermatitis.

#### **Serious eye damage/irritation**

Causes eye irritation.

#### **Respiratory or skin sensitization**

Vapors are irritating to mucous membrane and upper respiratory tract.

# Safety Data Sheet

## Nail Tek Quicken Top Coat

### Germ cell mutagenicity

No data available

### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

### Reproductive toxicity

No data available

### Summary of evaluation of the CMR properties

No data available.

### STOT-single exposure

CNS. May cause drowsiness or dizziness.

---

## SECTION 12: Ecological information

### Toxicity

Large volumes of this product may be harmful or fatal to aquatic life.

---

## SECTION 13: Disposal considerations

### Waste treatment methods

#### Disposal of the product

HOUSEHOLD WASTES: Follow applicable local and state household waste regulations. The regulations of US, EPA's Resource Conservation or Recovery Act are not applicable to household consumers. NON-CONSUMER WASTES: Waste disposal must follow US, Federal, State and Local regulations or Local Foreign Government applicable regulations. This product may be disposed of at a permitted facility or as advised by your local hazardous waste regulatory authority, if unaltered by use.

---

## SECTION 14: Transport information

### DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

### IMDG

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

### IATA

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

---

## SECTION 15: Regulatory information

# Safety Data Sheet

## Nail Tek Quicken Top Coat

Safety, health and environmental regulations/legislation specific for the substance or mixture

### Massachusetts Right To Know Components

Chemical name: Ethyl acetate  
CAS number: 141-78-6

### New Jersey Right To Know Components

Common name: ETHYL ACETATE  
CAS number: 141-78-6

### Pennsylvania Right To Know Components

Chemical name: Acetic acid ethyl ester  
CAS number: 141-78-6

### Massachusetts Right To Know Components

Chemical name: Butyl acetate  
CAS number: 123-86-4

### New Jersey Right To Know Components

Common name: n-BUTYL ACETATE  
CAS number: 123-86-4

### Pennsylvania Right To Know Components

Chemical name: Acetic acid, butyl ester  
CAS number: 123-86-4

### Massachusetts Right To Know Components

Chemical name: Isopropyl alcohol (mfg-strong acid process)  
CAS number: 67-63-0

### New Jersey Right To Know Components

Common name: ISOPROPYL ALCOHOL  
CAS number: 67-63-0

### Pennsylvania Right To Know Components

Chemical name: 2-Propanol  
CAS number: 67-63-0

### HMIS Rating

|                     |     |
|---------------------|-----|
| Health              | * 2 |
| Flammability        | 2   |
| Physical hazard     | 1   |
| Personal protection |     |

### NFPA Rating

|                   |   |
|-------------------|---|
| Health hazard     | 2 |
| Fire hazard       | 2 |
| Reactivity hazard | 1 |
| Special hazard    |   |

---

## SECTION 16: Other information

### Full text of hazard statements referenced in Section 2

|      |                                   |
|------|-----------------------------------|
| H319 | Causes serious eye irritation     |
| H335 | May cause respiratory irritation  |
| H336 | May cause drowsiness or dizziness |
| H225 | Highly flammable liquid and vapor |

## **Safety Data Sheet**

### **Nail Tek Quicken Top Coat**

#### **Further information/disclaimer**

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.